



Main

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCA LUCB LUCC LUCD LUCL LUCM
Device application	Communication
Range compatibility	TeSys TeSys U LUB non reversing power base TeSys TeSys U LU2B reversing power base

Complementary

Function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	RS485 multidrop
Bus type	Modbus
Cable connector type	RJ45 front panel
Communication port protocol	Modbus RTU
Addressing	0...31
Transmission rate	19200 bit/s
Return time	30 ms
Number of inputs	2
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	1 2 dedicated to starter-controller coil operation
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GG fuse 1 A
Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 2 cable 0.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.25...0.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.25...1 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.14...0.5 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 2 cable 0.14...0.75 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.25...0.34 mm ² - cable stiffness: flexible - with cable end
Associated cable type	AWG 26...AWG 16

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Tightening torque	0.2...0.25 N.m - with screwdriver 2.5 mm
Product weight	0.08 kg

Environment

ambient air temperature for operation	-25...55 °C
IP degree of protection	IP20 IEC 60529

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1036 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available