



## Main

Range of product	NSX100...250 NSX400...630 NSX100...250 DC NSX400...630 DC
Range	Compact
Device short name	2 early-make contacts
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	Compact - Compact NSX circuit breaker Compact - Compact NSX DC circuit breaker

## Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-make
Mounting mode	Drawout
[Ith] conventional free air thermal current	6 A
[Ie] rated operational current	DC-12 : 6 A DC 24 V DC-12 : 0.6 A DC 110 V AC-12 : 6 A AC 50/60 Hz 110 V AC-12 : 6 A AC 50/60 Hz 220/240 V AC-12 : 6 A AC 50/60 Hz 24 V AC-12 : 6 A AC 50/60 Hz 380/440 V AC-12 : 6 A AC 50/60 Hz 48 V AC-12 : 6 A AC 50/60 Hz 480 V AC-12 : 6 A AC 50/60 Hz 660/690 V AC-15 : 0.1 A AC 50/60 Hz 660/690 V AC-15 : 1.5 A AC 50/60 Hz 480 V AC-15 : 2 A AC 50/60 Hz 380/440 V AC-15 : 4 A AC 50/60 Hz 220/240 V AC-15 : 5 A AC 50/60 Hz 110 V AC-15 : 6 A AC 50/60 Hz 24 V AC-15 : 6 A AC 50/60 Hz 48 V DC-12 : 0.3 A DC 250 V DC-12 : 2.5 A DC 48 V DC-14 : 0.03 A DC 250 V DC-14 : 0.05 A DC 110 V DC-14 : 0.2 A DC 48 V DC-14 : 1 A DC 24 V
Minimum load	100 mA at 24 V DC

## Environment

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0818 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations