

LV429424

trip unit accessory - SDTAM 24/415V AC/DC - for
NSX100..250 / NSX400..630



Main

Range of product	NSX100...250 NSX400...630
Range	Compact
Device short name	SDTAM
Product or component type	Thermal fault module
Device application	Signalling
Range compatibility	Compact - Compact NSX circuit breaker
Accessory / separate part category	Trip unit accessory
Trip unit name	Micrologic 2.2 M Micrologic 2.3 M Micrologic 6.2 E-M Micrologic 6.3 E-M

Complementary

Maximum output current	0.08 A
[Us] rated supply voltage	24...415 V AC 24...415 V DC

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0818 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.