MB248DM2X15

MB Isobar Standard Distribution Board 48P C60 IP42 250A ORANGE



Main

| Range | Acti 9 |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name | Acti 9 isobar DB |
| Device short name | MB |
| Product or component type | Distribution board |
| Device application | Distribution |
| Enclosure type | Standard |
| Door type | External plain |
| Provided equipment | Door Enclosure Pole filler Earth/neutral terminal block 165 A Circuit schedule card Removable gland plates - top and bottom 2 keys TNA chassis |
| Colour | Orange |

Complementary

| [le] rated operational current 250 A Enclosure mounting Surface Poles description 3P + N Enclosure material Metal Number of ways 1 way(s) as incomer - 3P 48 way(s) as outgoer - 1P Number of poles 48 Nos. of for 18 mm pole capacity Enclosure material Metal Height 1000 mm Width 580 mm Depth 235 mm | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|------------------------------------|--|
| Poles description 3P + N Enclosure material Metal Number of ways 1 way(s) as incomer - 3P 48 way(s) as outgoer - 1P Number of poles 48 Nos. of for 18 mm pole capacity Enclosure material Metal Height 1000 mm Width 580 mm Depth 235 mm | [le] rated operational current | 250 A | |
| Enclosure material Number of ways 1 way(s) as incomer - 3P 48 way(s) as outgoer - 1P Number of poles 48 Nos. of for 18 mm pole capacity Enclosure material Metal Height 1000 mm Width 580 mm Depth 235 mm | Enclosure mounting | Surface | |
| Number of ways 1 way(s) as incomer - 3P 48 way(s) as outgoer - 1P Number of poles 48 Nos. of for 18 mm pole capacity Enclosure material Metal Height 1000 mm Width 580 mm Depth 235 mm | Poles description | 3P + N | |
| 48 way(s) as outgoer - 1P Number of poles 48 Nos. of for 18 mm pole capacity Enclosure material Metal Height 1000 mm Width 580 mm Depth 235 mm | Enclosure material | Metal | |
| Enclosure material Metal Height 1000 mm Width 580 mm Depth 235 mm | Number of ways | | |
| Height 1000 mm Width 580 mm Depth 235 mm | Number of poles | 48 Nos. of for 18 mm pole capacity | |
| Width 580 mm Depth 235 mm | Enclosure material | Metal | |
| Depth 235 mm | Height | 1000 mm | |
| | Width | 580 mm | |
| | Depth | 235 mm | |
| IP degree of protection IP42 | IP degree of protection | IP42 | |

Environment