

NSYPIN108

Internal door for Spacial WM encl.H1000xW800 steel, RAL7035.Adjustable in depth



Main

Range	Spacial
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Device application	Multi-purpose
Enclosure nominal dimensions	
Mounting location	Front side Step slide
Range compatibility	Spacial CRN Spacial S3D Spacial S3X
Device composition	1 door 4 fixing brackets 2 mounting uprights

Complementary

Material	Sheet steel for door
Colour	All faces : grey RAL 7035
Surface finish	Polyester powder
Lock type	Lock 3 mm double bar
Number of locks	1
Adjustment	Pitch 25 mm (on step slides)
Door type	Internal plain
Door opening side	Reversible
Maximum load	30 kg/m ²
Height	Nominal : 1000 mm
Width	Nominal : 800 mm
Product weight	10 kg

Environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.