# **NSYTBP241912HT**

PC box IP66 IK08 RAL7035 Int.H225W175D120 Ext.H241W194D127 Transp.cover H40





#### Main

Range	Thalassa
Product name	Thalassa TBP
Device application	Multi-purpose
Product or component type	Industrial box
Height	241 mm
Width	194 mm
Depth	127 mm
Internal height	225 mm
Internal width	175 mm
Internal depth	120 mm
Enclosure mounting	Wall mounted
Device composition	1 x body 1 x cover 4 x cover screw
Body type	One piece moulded
Type of front cover	High transparent cover
Cover fixing	Plastic screws
Lock type	Outside sealed area : flat screwdriver captive screw
Removable parts	Cover, by captive screws

### Complementary

Material	Polycarbonate	
Colour	Grey ( RAL 7035 ) Transparent	
Standards	IEC 62208 UL 508 A	
Product certifications	DEMKO SEMKO TÜV UL	
Electrical insulation class	Class II	
IP degree of protection	IP66 conforming to NEMA 4.4X	
IK degree of protection	IK08 conforming to IEC 62262	
Fire resistance	960 °C	
Ambient air temperature for storage	-1560 °C	
Ambient air temperature for operation	-2580 °C	
Product weight	0.82 kg	

## **Environment**

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
REACh	Reference contains SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations