



Main

Device short name	FDM121
Product or component type	Display module
Accessory / separate part category	Display and signalling accessory
Range compatibility	Compact Compact NS1600b...3200 Compact Compact NS630b...1600 Compact Compact NSX Masterpact Masterpact NT Masterpact Masterpact NW PowerPact PowerPact Multistandard PowerPact PowerPact H PowerPact PowerPact J PowerPact PowerPact L PowerPact PowerPact P PowerPact PowerPact R
Offer type	C4 C5
Product name	Enerlin'X FDM
Function of module	Remote control Metering Display alarm View network

Complementary

Control type	Remote control
Mounting mode	Flush mounting
Mounting support	Surface mount with kit
Display type	LCD screen with white backlighting
Display resolution	128 x 128 pixels
View angle horizontal x vertical	60 x 30°
[Us] rated supply voltage	24 V DC (- 20...10 %)
Current consumption	21 mA
Standards	CE CSA UL
Height	96 mm
Width	96 mm
Depth	30 mm
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Compact NS1600b...3200

Environment

IP degree of protection	IP54
ambient air temperature for operation	-10...55 °C
ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1749 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available

