VW3A3310D

Modbus TCP communication card - 1 RJ45 - 10/100 Mbps



Main

Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71 Altivar 61Q Altivar 71Q
Communication port protocol	Modbus TCP
Product specific application	For daisy chain mounting
Connector type	1 RJ45
Transmission rate	10 Mbps 100 Mbps
Physical interface	Ethernet 2
Web services	Altivar chart Altivar viewer Data editor E-mail Ethernet statistics FDR Agent IO Scanner Security

Complementary

Exchange mode	Half duplex and full duplex	
Communication data link	LLC : IEEE 802.2 MAC : IEEE 802.3	
Communication network type	IP conforming to RFC791	
Communication transport type	8 connections maximum TCP conforming to RFC793 UDP	
Concept	Transparent Ready class C20	
Web server	Embedded	
Communication service	CiA 402 profile Communication monitoring can be inhibited, adjustable Diagnostics (08) FTP I/O profile I/O scanning service can be inhibited Read device identification (43) Read holding registers (03) Read input registers (04) Read/write multiple registers (23) SNMP TFTP Write multiple registers (16) Write single register (06)	
Display type	1 LED for 10/100 Mbps (speed) 1 LED for FLT (Ethernet fault) 1 LED for RX (reception) 1 LED for STS (IP address) 1 LED for TX (transmission) Graphic display terminal for control word received Graphic display terminal for reference received Web server	
Product weight	0.3 kg	

Environment

