XSDH407339

inductive sensor XSD 80x80x40 - plastic - Sn40mm - 12..48VDC - terminals





Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XSD
Sensor design	Form 80 x 80 x 40
Size	40 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	4-wire
[Sn] nominal sensing distance	40 mm
Discrete output function	1 NO + 1 NC
Discrete output type	PNP
Electrical connection	Screw-clamp terminals
[Us] rated supply voltage	DC
IP degree of protection	IP67

Complementary

etection face	Frontal	
etector flush mounting acceptance	Non flush mountable	
aterial	Plastic	_ ;
ont material	Plastic	_
utput circuit type	DC	_ ,
able entry	1 entry tapped for Pg 13.5 cable gland	
vitching capacity in mA	<= 200 mA	_ ;
vitching frequency	<= 50 Hz	_ :
arking	CE	_ '
epth	40 mm	_ :
eight	100 mm	
dth	80 mm	_ :

Environment

product certifications	CCC	
ambient air temperature for operation	-2570 °C	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1136 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations