



Main

Commercial Status	Commercialised
Range of product	Harmony XB5
Product or component type	Head for illuminated double-headed pushbutton
Product compatibility	Integral LED
Device short name	ZB5
Bezel material	Plastic
Mounting diameter	22 mm
Sale per indivisible quantity	1
Shape of signaling unit head	Rectangular
Type of operator	Spring return
Operator profile	2 flush pushbuttons - 1 central pilot light
Operators description	Green "I" - red "O"

Complementary


Product weight	0.023 kg
Colour of marking	Black marking when white caps
Operator profile	Green flush, white I
Mechanical durability	1000000 cycles
Maximum of contact NO or NC	6
Station name	XALD 1 cut-out

Environment


Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class II conforming to IEC 60536
IP degree of protection	IP69 K IP66
NEMA degree of protection	NEMA 4X NEMA 13
Resistance to high pressure washer	7000000 Pa at 55 °C, distance: 0.1 m
IK degree of protection	IK05 conforming to IEC 50102
Standards	CSA C22-2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508
Product certifications	BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed
Vibration resistance	5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms half sine wave acceleration conforming to IEC 60068-2-27 30 gn for 18 ms half sine wave acceleration conforming to IEC 60068-2-27

Dimensions of Heads for Double-Headed Pushbuttons and Pilot Lights


ZB5 AW7A374•, ZB5 AW7A17••, ZB5 AW7A9



ZB5 AW7L374•



ZB5 AW7A374•, ZB5 AW7A17••, ZB5 AW7A9 + boot ZBA 708



ZB5 AW7L374• + boot ZBA 710

