

PRODUCT DATASHEET

DULUX S 11 W/O G23

OSRAM DULUX S | Short CFLni, with 2-pin base for CCG operation

AREAS OF APPLICATION

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

PRODUCT BENEFITS

- Extremely economical
- Good quality of light
- Extremely low profile
- Long service life
- Improved maintenance

PRODUCT FEATURES

- Average life: 10,000 h
- Color rendering index R_a for lamps with white light: 80...89
- Also available in red, green and blue
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



TECHNICAL DATA

Electrical data

Nominal wattage	11.00 W
Rated wattage	11.00 W

Photometrical data

Luminous flux	900 lm
Color rendering index Ra	80...89

Dimensions & weight

Diameter	12.0 mm
Overall length	237.0 mm
Length	237.0 mm
Length acc. to IEC standard	215 mm
Length with base excl. base pins/connection	214.00 mm
Outer bulb	T12X3

Lifespan

Nominal lamp life time	5000 h
Rated lamp life time	5000 h
Lifespan	10000 h ¹⁾

¹⁾ With CCG/LLCG

Additional product data

Base (standard designation)	G23
Mercury content	3.0 mg

EQUIPMENT / ACCESSORIES

– Suitable for operation on conventional control gear

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321664358	DULUX S 11 W/0 G23	Shipping carton box 10	123 mm x 78 mm x 252 mm	2.42 dm ³	519.00 g
4050300192512	DULUX S 11 W/0 G23	Shipping carton box 50	240 mm x 190 mm x 261 mm	11.90 dm ³	2456.00 g
4050300923956	DULUX S 11 W/0 G23	Shipping carton box 100	510 mm x 200 mm x 280 mm	28.56 dm ³	8510.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.