Catalogue No: 100-C12EJ10

CONTACTOR 5.5kW 3P 24V DC COIL 1NO AUXILIARY

Motor Control and Drives > Motor Starting and Protection > Contactors > Allen-Bradley Contactors > Bulletin 100-C Contactors > 3-Pole Contactors with DC Coil





Contactor 3 pole 12A 5.5kW 1N/O Auxiliary 24V DC Coil

- Available in AC or DC control coil versions to suit • application requirements
- Common accessories for all size contactors, minimising inventory and maximising flexibility
- Reversible (line or load side) coil terminations for total • flexibility
- DIN rail mountable for easy installation

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	100-C12
Component Type Motor Control and Drives	Standard Contactor
le, Rated Operational Current, AC-1, 415V, 40°C	32 A@415V,40°C
kW Rating, AC-3, 415V, 60°C	5.5 kW @415V, 60°C
le, Rated Operational Current, AC-3, 415V, 60°C	12 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	5.5 kW @690V, 60°C
le, Rated Operational Current, AC-3, 690V, 60°C	7 A@690V,60°C
Number of Poles	3
Contact Configuration, Main Poles	3 NO main poles
Contact Configuration, Auxiliary	1 NO auxiliary
Coil Type	Electronic w/ Integrated Diode type
Coil Voltage, DC, Nom	24 V DC
IP Rating	IP20
REFERENCES	
IECEx Certificate -	
Supplier Declaration of Conformity:	
Installation Guide: -	
User Manual: -	
Manufacturer Datasheet: -	
Manufacturer Catalogue & Product Selection:	