

Catalogue No: 100-C72DJ10

CONTACTOR 37kW 3P 24V DC COIL 1NO AUXILIARY

Motor Control and Drives > Motor Starting and Protection > Contactors > Allen-Bradley Contactors > Bulletin 100-C Contactors > 3-Pole Contactors with DC Coil



Representative Photo Only
(actual product may vary based on configuration selections)

Contactor 3 pole 72A 37kW 1N/O auxiliary 24V DC Coil

- Available in AC or DC control coil versions to suit application requirements
- Common accessories for all size contactors, minimising inventory and maximising flexibility
- Reversible (line or load side) coil terminations for total flexibility
- DIN rail mountable for easy installation

SPECIFICATIONS

Product Series	100-C72
Component Type Motor Control and Drives	Standard Contactor
Ie, Rated Operational Current, AC-1, 415V, 40°C	100 A@415V,40°C
kW Rating, AC-3, 415V, 60°C	40 kW @415V, 60°C
Ie, Rated Operational Current, AC-3, 415V, 60°C	72 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	40 kW @690V, 60°C
Ie, Rated Operational Current, AC-3, 690V, 60°C	42 A@690V,60°C
Number of Poles	3
Contact Configuration, Main Poles	3 NO main poles
Contact Configuration, Auxiliary	1 NO auxiliary
Coil Type	Conventional w/ Integrated Diode type
Coil Voltage, DC, Nom	24 V DC
IP Rating	IP20


REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **100-C72DJ10**

CONTACTOR 37kW 3P 24V DC COIL 1NO AUXILIARY

Motor Control and Drives > Motor Starting and Protection > Contactors > Allen-Bradley Contactors > Bulletin 100-C Contactors > 3-Pole Contactors with DC Coil



Dimension Diagram