Catalogue No: 1606-XLSDNET4

POWER SUPPLY DEVICENET HP 1PH 100-240VAC TO 24VDC 90W 4A

Power Distribution and Protection > Power Supplies and Transformers > Switched Mode Power Supplies > Allen-Bradley Switched Mode Power Supplies > Bulletin 1606-XLS Performance Series > 1606-XLS Performance Specialty Modules





Power supply, 91 W, 3.8 A

- Efficient power supplies which minimise heat output and reduce associated running costs
- Redundancy module options allow for backup power in critical applications
- The compact footprint maximises usable space with the panel

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	Bul. 1606-XLS
Component Type Power Distribution & Protection	Switched Mode Power Supply
Input Type	AC: 1-Phase
Input Frequency, Nom	50 / 60 Hz
Input Frequency, Min	47 Hz
Input Frequency, Max	63 Hz
In, Nominal Current	0.5 A
Inrush Current, Max	4.9 A
Un, Nominal Voltage, AC, L-L	230 V AC
Indicator Type	LED
Output Voltage, DC, Nom	24 V DC
Output Current, Rated (rms)	3.8 A
Pout, Real, Rated W	91 W
Ripple Voltage, P-P, Max	50 mVpp
Hold-Up Time, Min	43 ms
MTBF, Mean Time Before Failure, Min	581000 hours
Mounting	DIN-35 Rail Mount
IP Rating	IP20
Height	124 mm
Width	40 mm
Depth	117 mm
Weight	0.62 kg
Standards Compliance	UL 508 IEC 60950 EN 60950 EN 50178
Certifications	CE



Catalogue No: 1606-XLSDNET4

POWER SUPPLY DEVICENET HP 1PH 100-240VAC TO 24VDC 90W 4A



Power Distribution and Protection > Power Supplies and Transformers > Switched Mode Power Supplies > Allen-Bradley Switched Mode Power Supplies > Bulletin 1606-XLS Performance Series > 1606-XLS Performance Specialty Modules

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

