



MicroLogix 4 Channel Current/Voltage Analog Differential Bipolar Inputs

- Feature-rich functionality addresses a wide range of application
- Software keying prevents incorrect positioning within the system
- Finger-safe terminal blocks for I/O wiring
- Small footprint reduces panel space

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	MicroLogix Expansion I/O (Bul. 1762)
Component Type PLC & I/O	Analogue Input Module
Number of Analogue Inputs	4 qty
Analogue Input Type(s)	Current / Voltage: Differential
Analogue Input Range(s)	-10 ... 10V DC 4 ... 20mA
Analogue Resolution, Input	16 bit (signed)
Operating Temperature, Max	65 °C max
Operating Temperature, Min	-20 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing
Shock Acceleration (Max.)	30 g
Vibration Acceleration (Max.)	5 m/s ²
Vibration Displacement (Peak to Peak Max.)	0.381 mm
Vibration Frequency, Operational (Max.)	500 Hz

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-