Catalogue No: **194E-E32-1753**

LBS FRONT/DOOR ON-OFF 3P 32A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Allen-Bradley Load Break Switches > 194E Load Break Switches (16 to 100A) > Front / Door Mounting





LOAD BREAK SWITCH UL/IEC 194E DOOR MOUNT 3P 32A

- Suitable as At-Motor Disconnect Switch (UL508) useful for overseas application with added UL requirements
- Bulletin 194R also suitable as service entrance disconnecting (UL98) providing even greater application use
- Greater installation flexibility with selection of front/door or DIN/base mounting configurations (194E series only)
- Padlockable Handles Available (up to 3 padlocks) for added security
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage

SPECIFICATIONS	
Product Series	Bul. 194E
Operator Type	Off/On Switch (Isolator) type
Number of Poles	3
Ui, Rated Insulation Voltage	690 V (rms)
Uimp, Impulse Withstand Voltage	8 kV
le, Rated Operational Current, AC-21a, 415V	25 A@415V
le, Rated Operational Current, AC-21a, 690V	32 A@690V
kW Rating, AC-23a, 400V, 3ph	15 kW @400V
kW Rating, AC-23a, 690V, 3ph	15 kW @690V
Wire / Conductor Size, Flex Cable, Min	1 mm² min
Wire / Conductor Size, Flex Cable, Max	10 mm² max
Wire / Conductor Size, Rigid Cable, Min	1.5 mm² min
Wire / Conductor Size, Rigid Cable, Max	16 mm² max
Height	64 mm
Width	45 mm
Depth	60 mm
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	60 °C max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	80 °C max

Catalogue No: **194E-E32-1753**

LBS FRONT/DOOR ON-OFF 3P 32A





REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-