

# Catalogue No: **22B-D2P3N104**

## PF40 PANL 3P 400V .75KW NO EMC

Motor Control and Drives > Variable Speed Drives, Low Voltage > Compact Drives > PowerFlex Legacy Compact Drives & Accessories > PowerFlex 40 > IP20 Panel Mount 415V AC Three-Phase Drives



PowerFlex 40 AC Drive, 480V AC, 3PH, 2.3 Amps, 0.75 kW, 1 HP, Frame Size B, IP20 (Open), LED Display, Digital Keypad, No CE Compliant Filter, RS485

- 0...10V or 4...20mA analogue output for feedback or as reference for other drives
- Timer, counter and other logic functions can reduce hardware costs and simplifying control schemes
- Two analogue input channels and PID capability offer enhanced application flexibility
- Sensorless vector control to meet low speed torque demands helping to improve application performance
- Integral RS-485 communications with the options of EtherNet/IP™, DeviceNet™, ControlNet™ and a variety of third-party networks.

Representative Photo Only  
(actual product may vary based on configuration selections)

### SPECIFICATIONS

Shock Acceleration (Max.)	15 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	1 m/s <sup>2</sup>
Vibration Frequency, Operational (Max.)	2000 Hz

### REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-