

Catalogue No: **42GRU-9000-QD**

RETRO 10-30VDC RED 50mm-9m LO/DO PNP/NPN DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Photoelectric Sensors > Allen-Bradley Photoelectric Sensors > Retroreflective Sensors > Rectangular



PHOTOSWITCH Photoelectric Sensor, Standard (On / Off), Retroreflective, 9.14m (30ft), 10-40V DC, NPN/PNP Transistor, 4-pin DC Micro (M12) QD

- Comprehensive range of photoelectric sensing technologies available which include retroreflective, through-beam, diffuse, background suppression, clear object detection, colour detection and fibre-optics
- Extensive range of photoelectric sensors with laser light source available suitable for high precision applications
- Extensive range of housing styles and mounting options
- Specialised versions with IP69k rating available for high-pressure washdown applications in the food and beverage industry
- Specialised long-range laser sensors available for distance measurement applications
- Specialised versions available with IO-Link technology. This technology enables the data delivery from the sensor directly into a control system in a very efficient manner

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	42G / Series 9000
Component Type Field Switching & Sensing	Photoelectric Sensor
Sensing Mode	Retroreflective
Light source type	LED
Colour, light source	Red (660nm)
Beam Angle / Field of View	1.5 ° (degrees)
Material, Lens	PMMA / Acrylic / Perspex / Plexiglas (Polymethyl methacrylate)
Material, Body / Housing	PBT / PBTP / Valox material
Shape	Rectangular
Height	74.93 mm
Width	41.91 mm
Depth	40 mm
Orientation	Right Angle
Mounting (Multiple)	Threaded Base Mounting Bracket (Ordered Separately)
Thread Size	M30 x 1.5 size
Teach Mode / Sensitivity Adjustment	Single-Turn Knob / Potentiometer sensitivity
Sensing Distance, Min	50 mm min
Sensing Distance, Max	9100 mm max
Operating Range(s)	10 ... 30V DC
Ue, Rated Operational Voltage, DC, min	10 V DC
Ue, Rated Operational Voltage, DC, max	30 V DC
Switching Mode	Light or Dark Operate Selectable
Output Type	NPN & PNP
Load Current	0.25 A
Response Time (Off → On)	2 ms

Catalogue No: **42GRU-9000-QD**

RETRO 10-30VDC RED 50mm-9m LO/DO PNP/NPN DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Photoelectric Sensors > Allen-Bradley Photoelectric Sensors > Retroreflective Sensors > Rectangular



Response Time (On → Off)	2 ms
Indicators	Red LED Green LED Yellow LED
Connection / Termination	M12 x 1, DC Micro, 4-pin
Number of Conductors	4 qty
Operating Temperature, Min	-34 °C min
Operating Temperature, Max	70 °C max
Relative humidity, min	5 %RH
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing
IP Rating	IP67 IP69K
Shock Acceleration (Max.)	30 g
Shock Duration (Max.)	1 ms
Shock Rating	IEC 60947-5-2
Vibration Displacement (Peak to Peak Max.)	1 mm
Vibration Frequency, Operational (Max.)	55 Hz
Vibration Rating	IEC 60947-5-2


REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	42GRU9000QD_ManufacturerDatasheet
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **42GRU-9000-QD**

RETRO 10-30VDC RED 50mm-9m LO/DO PNP/NPN DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Photoelectric Sensors > Allen-Bradley Photoelectric Sensors > Retroreflective Sensors > Rectangular



Technical Diagram