

Catalogue No: **440H-E22027**

HINGE SW 2NC SAFETY 1NO AUX SHAFT 80 x 10mm M16 CONDUIT

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley Mechanical Interlocks > Hinge switches



Hinge Switch - Ensign 3: Contacts: (Safety/Aux) 2 Normally Closed / 1 Normally Closed, BBM Preference: Break Before Make, Actuator Shaft: Length: 80MM Diameter: 10MM-Solid, Conduit Entry: M16 Conduit

- Available in tongue-interlocking or solenoid-based guard interlocking types
- Heads are rotatable for optimum mounting flexibility
- Suitable for sliding, hinged or lift-off guards

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Safety Switch Type	Hinge Switch type
Number of Safety Contacts	2 qty safety
Output Configuration, Safety	2 NC
Number of Aux Contacts	1
Output Configuration, Auxiliary	1 NO
Conduit Entry	M16 entry
Actuator Included	Yes Y / N
Actuator Type	Solid Shaft
Material, Body / Housing	Glass-Filled PBT / Valox material
IP Rating	IP67

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-