



Sipa 2 Control Unit 24V AC/DC, 110/230V AC 2NO Safety Outputs 1NC-Auxiliary outputs, 45mm housing

- Extensive range of different housing styles and mounting options
- RFID coded devices available
- Stainless steel versions available which are suitable for use in harsh environments
- Plastic or metal housing versions available
- Cabling for this range can be found in **Section 12 "Terminals and Pre-Wired Cables"**

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--|--|
| InterlockType | Sipa |
| B10d (ISO 13849:2006) | 2000000 |
| MTTFd (ISO 13849:2006) | 385 years |
| Safety Category(s) (ISO13849:1999 / EN954) | EN 954 / ISO 13849:1999 Category 3 ISO 130849:1999 |
| Safety Category | Cat 3 safety |
| Housing Type | Rectangular |
| Material, Body / Housing | ABS material |
| Output Configuration, Safety | 2 NO |
| Output Configuration, Auxiliary | 1 NC |
| Operating Temperature, Max | 55 °C max |
| Operating Temperature, Min | -10 °C min |
| Storage Temperature, Max | 55 °C max |
| Storage Temperature, Min | -10 °C min |
| IP Rating | IP67 |
| Shock Acceleration (Max.) | 30 g |
| Shock Duration (Max.) | 11 ms |
| Standards Compliance | EN 954 / ISO 13849:1999 Category 1 NFPA 79 EN 1088 IEC 60947-5-1 EN 60947-5-1 EN 60947-5-3 ANSI B11.19 AS/NZS 4024 Category 1 |

Catalogue No: **440N-S32021**

SIPHA 2 CONTROL UNIT AC/DC 2NO-SFTY 1NC-AUX

Safety > Safety Interlocks > Non-Contact Interlocks > Allen-Bradley 440N Non-Contact Interlock Switches > Sipha > Sipha control units



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: [440N_Manufacturer Catalogue](#)