



Representative Photo Only
(actual product may vary based on configuration selections)

MSR126.IT 24V AC/DC 2NC Inputs 2NO Safety Outputs Auto-manual Reset

- Support a wide variety of input devices and output configurations
- Compact packages with removable terminals
- Ideal for relatively small safety applications and single zone control
- Available in electromechanical versions or solid-state models

SPECIFICATIONS

Product Series	Bul. 440R - MSR126.IT
Safety stop category(s) (IEC/EN 60204-1)	IEC/EN 60204-1 Stop Category 0
Safety Stop Category	Stop Cat 0 safety
Safety Performance Level(s) (ISO13849:2006)	ISO 13849:2006 PLe ISO 13849:2006
Safety Performance Level	PLe safety
MTTFd (ISO 13849:2006)	398 years
SIL Claim(s) - Machinery (IEC/EN 62061)	IEC/EN 62061 SILCL3 IEC/EN 62061
SIL Claim, Machinery	SIL CL 3 machinery
Safety Category(s) (ISO13849:1999 / EN954)	EN 954 / ISO 13849:1999 Category 4 ISO 130849:1999
Safety Category	Cat 4 safety
Reset Type	Automatic / Manual
Terminal Type	Fixed (non-removable) Terminal Block
Mounting	DIN-35 Rail Mount
Material, Body / Housing	Nylon / PA6 / PA66 (Polyamide 6) material
Indicator Type	LED
Colour, Indicator	Green
Inputs	2 NC
Output Configuration, Safety	2 NO
Power ON delay	3 s
Response Time (Off → On)	15 ms
Unom, Supply Voltage, AC, Nom	24 V AC
Unom, Supply Voltage, DC, Nom	24 V DC
Switching current, Min	10 mA
Ie, Rated Operational Current, AC-1, 250V	6 A@250V
Ie, Rated Operational Current, AC-15, 250V	6 A@250V
Ie, Rated Operational Current, DC-1, 24V	6 A@24V
Ie, Rated Operational Current, DC-13, 24V	3 A@24V
Power Consumption, Max	4 W

Catalogue No: **440R-N23114**

MSR126.IT 24VAC/DC 2NC-IN 2NO-SFTY AM

Safety > Safety Controllers > Single Function Safety Relays > Allen-Bradley MSR Safety Relays > Single Function > Automatic / Manual Reset



Overvoltage Category	III
Wire / Conductor Size (Min)	0.20 mm ² min
Wire / Conductor Size (Max)	4 mm ²
Uimp, Impulse Withstand Voltage	2.5 kV
Tightening Torque, Nominal	0.8 Nm
Pollution Degree	2
Operating Temperature, Max	55 °C max
Operating Temperature, Min	-5 °C min
IP rating, body / housing	IP40
IP Rating, Terminals	IP20
Material, Contacts	Silver Tin Oxide (AgSnO ₂) material
Mechanical Service Life	2000000 cycles
Height	75 mm
Width	22.5 mm
Depth	110 mm
Weight	0.16 kg
Shock Acceleration (Max.)	10 g
Shock Duration (Max.)	16 ms
Vibration Displacement (Peak to Peak Max.)	0.35 mm
Vibration Frequency, Operational (Max.)	55 Hz
Standards Compliance	ANSI B11.19
Certifications	CE C-Tick C-UL-US

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	440RN23114_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	440RN23114_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-