

Interposing/Isolation Relays

Product Overview/Product Selection



Bulletin 700-HP — (PCB) "Pin Style" Relay

- 8 A contact ratings
- DPDT/ (2 c/o) contacts
- Plug-in PIN style (PCB) terminals (5 mm pinning)
- Choice of standard silver nickel contacts, or silver nickel with gold-plated contacts

Table of Contents

Product Selection this page

Accessories..... 9-59

Specifications..... 9-60

Approximate Dimensions..... 9-61

Standards Compliance and Certifications

See Specification table in this section, page 9-60.

Product Selection

Slim Line Relay with "PIN Style" Terminations

	Description	Contact Rating	Wiring Diagrams		Coil Voltage	Package Quantity	Cat. No.
			U.S./Canada	International			
	DPDT 2-Pole 2 Form C AgNi + Au Gold Plated Contacts Sockets	8 A			6V AC	10	700-HPX2A06
					12V AC	10	700-HPX2A12
					24V AC	10	700-HPX2A24
					120V AC	10	700-HPX2A1
					240V AC	10	700-HPX2A2
					6V DC	10	700-HPX2Z06
	12V DC	10	700-HPX2Z12				
	24V DC	10	700-HPX2Z24				
	48V DC	10	700-HPX2Z48				
	110V DC	10	700-HPX2Z1				
	DPDT 2-Pole 2 Form C AgNi Contacts Sockets	8 A			6V AC	10	700-HP32A06
					12V AC	10	700-HP32A12
					24V AC	10	700-HP32A24
					120V AC	10	700-HP32A1
					240V AC	10	700-HP32A2
					6V DC	10	700-HP32Z06
	12V DC	10	700-HP32Z12				
	24V DC	10	700-HP32Z24				
48V DC	10	700-HP32Z48					
110V DC	10	700-HP32Z1					
Bulletin 700-HP DPDT	Sockets		700-HN123	700-HN123			

