## Catalogue No: 800F-N3W

#### LED MODULE LATCH MOUNT 24V WHITE

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Integrated Lamp Modules for use with Pilot Lights > Integrated LED Modules, 24V AC/DC:





Representative Photo Only (actual product may vary based on configuration selections)

#### INTEGRATED WHITE LED MODULE 24V AC/DC

- The 800F line of 22.5 mm push buttons is designed and manufactured to demanding performance specifications to ensure you receive optimized durability and performance.
- 800FP operators are made of industrial grade thermoplastic for superior chemical resistance.
- 800FM operators are constructed of tough die cast zinc alloy, finished with chromate plating that can be used in the most arduous applications.

SPECIFICATIONS	
Product Series	800F
Component Type Pushbutton and Pilot Lights	Lamp Module
Un, Nominal Operational Voltage, AC	24 V AC
Ubmin, Service Voltage, AC, Min	10 V AC
Ubmax, Service Voltage, AC, Max	29 V AC
Un, Nominal Operational Voltage, DC	24 V DC
Ubmin, Service Voltage, DC, Min	10 V DC
Ubmax, Service Voltage, DC, Max	30 V DC
Rated Frequency	50 / 60 Hz
Lamp Holder	Integrated Lamp Module
Colour, Lamp	White colour
Luminous Intensity	360 mcd
Terminal Type	Screw Terminal(s)
RoHS Approved	Yes
CE Marked	Yes
Operating Temperature, Max	70 °C max
Operating Temperature, Min	-25 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative humidity, min	50 %RH
Relative Humidity, Max	95 %RH
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 m/s²
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Vibration Duration (Max.)	180 min

# Catalogue No: 800F-N3W

### LED MODULE LATCH MOUNT 24V WHITE



Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Integrated Lamp Modules for use with Pilot Lights > Integrated LED Modules, 24V AC/DC

Standards Compliance	NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1 ISO 13850	
Certifications	UR UL CSA CCC CE RoHS	
Shipping Approvals	ABS (American Bureau of Shipping)	
REFERENCES		
IECEx Certificate	-	
Supplier Declaration of Conformity:	-	
Installation Guide:	-	
User Manual:	-	
Manufacturer Datasheet:	800FN3W_Manufacturer Datasheet	
Manufacturer Catalogue & Product Selection:	800FN3W_Manufacturer Product Selection Guide	

