

Catalogue No: **800F-PN3W**

INTEGRATED LED MODULE PLM 24V WHITE

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Integrated Lamp Modules for use with Pilot Lights > Integrated LED Modules, 24V AC/DC



INTEGRATED LED MODULE 24V AC/DC WHITE



Representative Photo Only
(actual product may vary based on configuration selections)

- The 800F range of 22.5mm operator control devices includes a diverse range of products making it suitable for use in a wide range of applications. Products in the range include pushbuttons, selector switches, pilot lights, emergency stop operators and more.
- Operators are available in both plastic (800FP) and metal (800FM) variants.

SPECIFICATIONS

| | |
|--|---|
| Product Series | 800F |
| Component Type Pushbutton and Pilot Lights | Lamp Module |
| Un, Nominal Operational Voltage, AC | 24 V AC |
| Ubmin, Service Voltage, AC, Min | 10 V AC |
| Ubmax, Service Voltage, AC, Max | 29 V AC |
| Un, Nominal Operational Voltage, DC | 24 V DC |
| Ubmin, Service Voltage, DC, Min | 10 V DC |
| Ubmax, Service Voltage, DC, Max | 30 V DC |
| Rated Frequency | 50 / 60 Hz |
| Lamp Holder | Integrated Lamp Module |
| Colour, Lamp | White colour |
| Luminous Intensity | 360 mcd |
| Material, Coupling Plate | Glass-Filled Nylon / PA6 / PA66 (Polyamide 6) |
| RoHS Approved | Yes |
| CE Marked | Yes |
| Operating Temperature, Max | 70 °C max |
| Operating Temperature, Min | -25 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -40 °C min |
| Relative Humidity, Min | 50 %RH |
| Relative Humidity, Max | 95 %RH |
| Shock Acceleration (Max.) | 100 g |
| Shock Duration (Max.) | 11 ms |
| Vibration Acceleration (Max.) | 10 m/s ² |
| Vibration Displacement (Peak to Peak Max.) | 1.52 mm |
| Vibration Frequency, Operational (Max.) | 2000 Hz |
| Vibration Duration (Max.) | 180 min |

Catalogue No: **800F-PN3W**
INTEGRATED LED MODULE PLM 24V WHITE

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800F Pushbuttons and Pilot Lights > 800F Integrated Lamp Modules for use with Pilot Lights > Integrated LED Modules, 24V AC/DC



| | |
|----------------------|--|
| Standards Compliance | NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 IEC 60947-1 ISO 13850 |
| Certifications | UR UL CSA CCC CE RoHS |
| Shipping Approvals | ABS (American Bureau of Shipping) |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | 800FPN3W_Manufacturer Datasheet |
| Manufacturer Catalogue & Product Selection: | 800FPN3W_Manufacturer Product Selection Guide |