Catalogue No: **800T-N310** PROTECTIVE GUARD 800T/H 2P PUSH PULL 40mm STAINLESS STEEL

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800T/800H Pushbuttons > Accessories > Guards





Guard For 800T/H Push Pull 40mm Stainless Steel

- 800T (metal) and 800H (plastic) 30.5 mm product lines are designed and constructed to perform in the most demanding industrial environments.
- Button caps made from thermoplastic polyester resin and deliver excellent resistance to corrosive agents and ensure color identification is never lost.
- Operator bushings are made from die cast zinc alloy giving strength and stability in installation.
- Riveted construction of the operator bushing, diaphragm seal and base plate, by four secure steel rivets, provides increased durability and tamper resistance.

Representative Photo Only

(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	800T
Component Type Pushbutton and Pilot Lights	Accessories - General
Compatible Product Series'	800T / H
Material	Stainless Steel
Details, text	Protective ring for 2-position push-pull operators (Illuminated or non- illuminated). Often used to avoid unintentional tripping of E-stop operators.
Diameter	40 mm
Operating Temperature, Max	55 °C max
Operating Temperature, Min	-40 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Min	50 %RH
Relative Humidity, Max	95 %RH
Shock Acceleration (Max.)	100 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	10 m/s ²
Vibration Displacement (Peak to Peak Max.)	1.52 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Standards Compliance	UL 508 CSA C22.2 No. 14 EN 60947-5-1 EN 60947-5-5 ISO 13850
Certifications	CE CSA UL CCC



Catalogue No: 800T-N310

PROTECTIVE GUARD 800T/H 2P PUSH PULL 40mm STAINLESS STEEL

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800T/800H Pushbuttons > Accessories > Guards

