### Catalogue No: 800T-T2H3

### TOGGLE SW 30.5mm 2W U & D SR

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800T/800H Pushbuttons > Toggle Switches > 2 Way, Metal





#### Toggle Switch 30.5mm Metal 2 Position Sr Operator Only

- 800T (metal) and 800H (plastic) 30.5 mm product lines are designed and constructed to perform in the most demanding industrial environments.
- Button caps made from thermoplastic polyester resin and deliver excellent resistance to corrosive agents and ensure color identification is never lost.
- Operator bushings are made from die cast zinc alloy giving strength and stability in installation.
- Riveted construction of the operator bushing, diaphragm seal and base plate, by four secure steel rivets, provides increased durability and tamper resistance.

Representative Photo Only (actual product may vary based on configuration selections)

| SPECIFICATIONS |  |
|----------------|--|
|                |  |

| SPECIFICATIONS                             |   |
|--|---|
| Product Series                             | 800T  |
| Component Type Pushbutton and Pilot Lights | Toggle Switch   |
| Number of Positions                        | 2   |
| Operator Action                            | Spring Return action  |
| Contact Block Included                     | No  |
| Material, Bezel                            | Zinc  |
| Electrical Service Life at Un, In          | 1000000 cycles  |
| Mechanical Service Life                    | 200000 cycles   |
| Operating Temperature, Max                 | 55 °C max   |
| Operating Temperature, Min                 | -40 °C min  |
| Storage Temperature, Max                   | 85 °C max   |
| Storage Temperature, Min                   | -40 °C min  |
| Relative Humidity, Min                     | 50 %RH  |
| Relative Humidity, Max                     | 95 %RH  |
| IP Rating                                  | IP66<br>IP65  |
| Shock Acceleration (Max.)                  | 100 g   |
| Shock Duration (Max.)                      | 11 ms   |
| Vibration Acceleration (Max.)              | 10 m/s <sup>2</sup>   |
| Vibration Displacement (Peak to Peak Max.) | 1.52 mm   |
| Vibration Frequency, Operational (Max.)    | 2000 Hz   |
| Standards Compliance                       | UL 508<br>CSA C22.2 No. 14<br>EN 60947-5-1<br>EN 60947-5-5<br>ISO 13850 |
| Certifications                             | CE<br>CSA<br>UL<br>CCC  |



# Catalogue No: 800T-T2H3

#### TOGGLE SW 30.5mm 2W U & D SR

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800T/800H Pushbuttons > Toggle Switches > 2 Way, Metal



| REFERENCES                                     |                                  |
|--|----------------------------------|
| IECEx Certificate                              | -                                |
| Supplier Declaration of<br>Conformity:         | -                                |
| Installation Guide:                            | -                                |
| User Manual:                                   | -                                |
| Manufacturer Datasheet:                        | 800T/800H_Manufacturer Datasheet |
| Manufacturer Catalogue<br>& Product Selection: | 800TT2H3_Manufacturer Catalogue  |



## Catalogue No: 800T-T2H3

#### TOGGLE SW 30.5mm 2W U & D SR

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Allen-Bradley 800T/800H Pushbuttons > Toggle Switches > 2 Way, Metal



|             |                | Handle Position |          |           |          | Туре | 4/13                    |                      |  |
|-------------|----------------|-----------------|----------|-----------|----------|------|-------------------------|----------------------|--|
|             |                |                 |          |           |          |      | Spring Return Operation | Maintained Operation |  |
|             |                |                 | $\Theta$ | $\bullet$ | $\Theta$ |      |                         |                      |  |
| Switch Type | Lever Movement | Up              | Left     | Center    | Right    | Down | Cat. No.                | Cat. No.             |  |
|             | <b></b>        | Х               | —        | 0         | —        | 0    | 800T-T2H3EEXX           | 800T-T2H1EEXX        |  |
| 2 Way       |                | 0               | _        | 0         | _        | x    |                         |                      |  |
|             |                |                 | Х        | 0         | 0        | _    | 900T TOFODDYY           | MANT TOPADDYY        |  |
|             |                |                 | 0        | 0         | Х        | —    | 800T-T2F3DDXX           | 800T-T2F1DDXX        |  |
|             |                |                 | Х        | 0         | 0        | 0    | 0                       |                      |  |
| 4.14/       |                | 0               | Х        | 0         | 0        | 0    | 800T-T4T8AAXX 800       |                      |  |
| 4 Way       |                | 0               | 0        | 0         | Х        | 0    |                         | 800T-T4R1AAXX        |  |
|             |                | 0               | 0        | 0         | 0        | Х    |                         |                      |  |

Technical Diagram

