

Catalogue No: 802T-ATPDS6

SPR-RTN-LVR SAFETY 2NO/2NC CW/CCW 0.45NM 13DEG M20

Field Switching and Sensing > Limit Switch > Limit Switches > Allen-Bradley Limit Switches > Bulletin 802T NEMA-Style Safety Limit Switches



Safety Limit Switch, Lever Type (lever not included), Spring Return, 2 N.C., 2 N.O., 13° travel to operate contacts, M20 conduit

- Factory sealed versions for demanding industrial environments
- Complete range of IEC style solutions for both safety and standard sensing applications
- Wide range of operating voltages and current ratings
- Extensive range of different housing styles and mounting options
- Wide variety of operating heads and levers

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	802T NEMA Safety Limit Switch
Contact Configuration	2 NO + 2 NC
Contact Action	Snap Action action
Actuator Action	Spring Return action
Current Rating (AC 15 240Vac)G	10 A
Conduit Entry	M20 entry
Material, Body / Housing	Metal material
Height	103.4 mm
Width	41.3 mm
Depth	70.8 mm
Operating Temperature, Max	110 °C max
Operating Temperature, Min	-18 °C min
IP Rating	IP67
Vibration Displacement (Peak to Peak Max.)	0.15 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Standards Compliance	EN 954 / ISO 13849:1999 Category 1 NFPA 79 IEC 60947-5-1 EN 1088 EN 60947-5-1 ANSI B11.19 AS/NZS 4024 Category 1
Certifications	CE C-UL-US

Catalogue No: **802T-ATPDS6**

SPR-RTN-LVR SAFETY 2NO/2NC CW/CCW 0.45NM 13DEG M20

Field Switching and Sensing > Limit Switch > Limit Switches > Allen-Bradley Limit Switches > Bulletin 802T NEMA-Style Safety Limit Switches



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -