



Limit Switch, NEMA Type 4 and 13 Oiltight Construction, Plug-In, Lever Type, Spring Return, Neutral Position, 4-Circuit

- Factory sealed versions for demanding industrial environments
- Complete range of IEC style solutions for both safety and standard sensing applications
- Wide range of operating voltages and current ratings
- Extensive range of different housing styles and mounting options
- Wide variety of operating heads and levers

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--|-------------------------------------|
| Product Series | 802T Low-Energy |
| Component Type Field Switching & Sensing | Limit Switch, Complete, No Operator |
| Contact Configuration | 2 NO + 2 NC |
| Contact Action | Snap Action action |
| Actuator Action | Spring Return action |
| Conduit Entry | 1/2" - 14NPT entry |
| Material, Body / Housing | Metal material |
| Height | 115.44 mm |
| Width | 41.28 mm |
| Depth | 71.35 mm |
| Safety Application Suitable | No |
| Operating Temperature, Max | 110 °C max |
| Operating Temperature, Min | -18 °C min |
| IP Rating | IP67 |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |