Catalogue No: 855E-24TL4

STACK LIGHT STEADY LED 24V AC/DC SOCKET MOUNT RED

Signalling Devices > Sight Indication > Stack Lights > Allen-Bradley Stack Lights > Allen-Bradley 855E 50mm Tower Lights > Light Modules



Control Tower Stack Light, 24V AC/DC, Steady Socket - Mount LED, Red Lens

- Available in a multitude of stackable colour configurations that allows you to provide multi-status indication of your application as required.
- Various sizes including 30,40,50,60 and 70mm diameter with either flashing or static modules that provides a versatile solution which can be adapted to your requirements.
- Possible to stack up to 5 high(856T 7 high) with the option of including a Piezo buzzer to combine visual and audio signalling for best effect.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Signalling	Light Module
Un, Nominal Operational Voltage, AC	24 V AC
Un, Nominal Operational Voltage, DC	24 V DC
Operating Range Units	V AC/DC
Lamp Module Included	Yes
Lamp Type	LED type
Illumination Mode	Steady
Luminous Intensity	2240 mcd
Colour, Body / Housing	Black colour
Current Draw	29 mA
Colour, Lens	Red colour
Material, Lens	PC (Polycarbonate)
Material	PC (Polycarbonate)
Diameter, Base	52 mm
Height	67.7 mm
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	50 °C max
Wire / Conductor Size (Min)	0.5 mm² min
Wire / Conductor Size (Max)	1.5 mm²
Tightening Torque, Nominal	0.87 Nm
NEMA Enclosure Class (NEMA 250:2003)	Type 13 Type 4 Type 4X
Material, Gasket / Seal	NBR (Acrylonitrile-butadiene rubber / Nitrile rubber) material
Service Life	100000 hours
IΔn, Leakage Current, Max	3 mA



Catalogue No: 855E-24TL4

STACK LIGHT STEADY LED 24V AC/DC SOCKET MOUNT RED





Standards Compliance	EN 60947-1 EN 60947-5-1 IEC 60947-1 IEC 60947-5-1 UL 508 CSA C22.2 No. 14
Certifications	CE C-UL-US
REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

