Catalogue No: 872C-D8NP18-D4

PROX 18mm 10-30VDC 8mm UNSHLD NO PNP 3WIRE DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Proximity Sensors > Allen-Bradley Proximity Sensors > Inductive Proximity Sensors > 18mm Cylindrical



Inductive Proximity Sensor, 3-Wire DC Standard Barrel, 18mm Diameter, Tubular:Nickel Plated Brass, 8mm Sensing Distance, Unshielded, N.O., Source (PNP) Output, Micro QD (DC)

- Inductive sensors provide reliable detection of metal objects
- Ultrasonic sensors provide long distance sensing in applications unsuitable for a photoelectric sensor
- Capacitive sensors provide optimum flexibility in level sensing applications
- Available in a wide range of housings to suit everything from light-duty applications through to harsher washdown or welding applications

Representative Photo Only (actual product may vary based on configuration selections)

uct Series	872C General Purpose
oonent Type Field Switching & Sensing	Proximity Sensor
ing Mode	Inductive
ded	No
e	Cylindrical - Threaded
eter	18 mm
th	76.5 mm
tation	Straight Through
nting (Multiple)	Mounting Nuts (Included) Mounting Bracket (Ordered Separately)
h Mode / Sensitivity Adjustment	No sensitivity
ing Distance	8 mm
Rated Operational Voltage, DC, min	10 V DC
Rated Operational Voltage, DC, max	30 V DC
hing Mode	N/O
ut Type	PNP
hing/Operating Frequency	1500 Hz
per of Conductors	3 qty
ection / Termination	M12 x 1, DC Micro, 4-pin
rial, Body / Housing	Nickel-Plated Brass material
ating Temperature, Max	70 °C max
ating Temperature, Min	-25 °C min
ating	IP67

Catalogue No: 872C-D8NP18-D4

PROX 18mm 10-30VDC 8mm UNSHLD NO PNP 3WIRE DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Proximity Sensors > Allen-Bradley Proximity Sensors > Inductive Proximity Sensors > 18mm Cylindrical



REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

