Catalogue No: 872C-DH8NP18-D4

PROX 18mm-SHORT 10-30VDC 8mm UNSHLD NO PNP 3WIRE DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Proximity Sensors > Allen-Bradley Proximity Sensors > Inductive Proximity Sensors > 18mm Cylindrical





Inductive Proximity Sensor, 3-Wire DC, Short Barrel, 18mm Diameter, Tubular:Nickel Plated Brass, Short, 8mm Sensing Distance, Unshielded, N.O., Source (PNP) Output, Micro QD (DC)

- Inductive sensors provide reliable detection of metal objects
- Ultrasonic sensors provide long distance sensing in applications unsuitable for a photoelectric sensor
- Capacitive sensors provide optimum flexibility in level sensing applications
- Available in a wide range of housings to suit everything from light-duty applications through to harsher washdown or welding applications

Representative Photo Only (actual product may vary based on configuration selections)

| SPECIFICATIONS | |
|--|--|
| Product Series | 872C General Purpose |
| Component Type Field Switching & Sensing | Proximity Sensor |
| Sensing Mode | Inductive |
| Shielded | No |
| Shape | Cylindrical - Threaded |
| Diameter | 18 mm |
| Length | 61.7 mm |
| Orientation | Straight Through |
| Mounting (Multiple) | Mounting Nuts (Included) Mounting Bracket (Ordered Separately) |
| Teach Mode / Sensitivity Adjustment | No sensitivity |
| Sensing Distance | 8 mm |
| Ue, Rated Operational Voltage, DC, min | 10 V DC |
| Ue, Rated Operational Voltage, DC, max | 30 V DC |
| Switching Mode | N/O |
| Output Type | PNP |
| Switching/Operating Frequency | 1500 Hz |
| Number of Conductors | 3 qty |
| Connection / Termination | M12 x 1, DC Micro, 4-pin |
| Material, Body / Housing | Nickel-Plated Brass material |
| Operating Temperature, Max | 70 °C max |
| Operating Temperature, Min | -25 °C min |
| IP Rating | IP67 |



Catalogue No: 872C-DH8NP18-D4

PROX 18mm-SHORT 10-30VDC 8mm UNSHLD NO PNP 3WIRE DC-MICRO-4

Field Switching and Sensing > Non Contact Sensors > Proximity Sensors > Allen-Bradley Proximity Sensors > Inductive Proximity Sensors > 18mm Cylindrical



| REFERENCES | |
|---|---|
| IECEx Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |