Free Call (Sales): 0800 558 055 sales@thehydrotapcompany.com www.thehydrotapcompany.com



Tempo Tronic Over-Sink Boiling Water

Boiling water when you need it for kitchens large or small.

Whether you're making tea or cooking pasta, the availability of boiling water when needed is convenient, time-saving and cost effective.

Benefits

When you need it - boiling water available as soon as you need it

Suits your needs - choose from models delivering 8 to 150 cups of boiling water

Convenient – two-way tap makes it easy to fill cups or jugs

Low maintenance - with a stainless steel case and interior tank, it is designed to last

Filter option available - can be supplied with an external 5-micron filter for fresh and healthy filtered boiling water (highly recommended)

Replacement Filter Cartridges -

- 1311046 for all models





	CAPACITY*			POWER		WATER PRESSURE		DIMENSIONS		
MODEL	Boiling Water Delivery	Boiling Water Capacity	Boiling Water Recovery	Rating	Supply Voltage	Min.	Max.	h	W	$d^{^{\dagger}}$
1070073 - 1.5L	8 Cups	1.5 Litres	90 Cups/Hr	6.8 Amps	220-240	1 Bar	7 Bars	335	268	170
1070074 - 2.5L	15 Cups	2.5 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	430	315	210
1070076 - 5L	30 Cups	5 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	510	365	240
1070078 - 7.5L	45 Cups	7.5 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	510	365	240
1070080 - 10L	60 Cups	10 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	565	425	310
1070082 - 15L	100 Cups	15 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	565	425	310
1070084 - 20L	120 Cups	20 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	630	490	340
1070086 - 25L	150 Cups	25 Litres	120 Cups/Hr	10 Amps	220-240	2 Bars	10 Bars	630	490	340

^{*}Cup 167ml and glass 200ml. Installation with an external water filter is recommended for protection of the heater and users. Installation with a water filter inhibiting the accumulation of mineral scale is essential in known hard water areas and a sediment filter is essential where water contains excessive sediment. † Depth includes tap.

Birko Heaters (Aust) Pty Ltd has a policy of continuous product improvement and reserves the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. This information is correct at the time of printing and is subject to change without prior notice. Warning: Products may be the subject of registered designs and patents. All Birko products should be installed in accordance with Birko installation instructions provided. Where stipulated Birko products must be installed by qualified tradepersons. Sizes quoted in this product specification sheet are approximate only.

Z010907