

Catalogue No: **150-F135NBR**

SMC-FLEX SOFT STARTER 480V 135A ND3W 24V AC/DC CONTROL

Motor Control and Drives > Soft Starters, Low Voltage > Industrial Soft Starters > Allen-Bradley LV Soft Starters > SMC-Flex Soft Starters > IP00 / IP20 Panel Mount - 200...415V AC Three-Phase with 24V AC/DC Control Power



Representative Photo Only
(actual product may vary based on configuration selections)

Soft starter 135A, with motor protection, supply voltage 480V AC, control voltage 24V AC/DC

- Modular for simplified installation and maintenance
- Built-in LCD and keypad or personal computer (PC) software setup, for process optimisation
- Integrated bypass minimises heat generation
- Nine start/stop modes and three slow-speed modes to suit application requirements
- Full metering and diagnostics for peace of mind

SPECIFICATIONS

Product Series	SMC-Flex (Bul. 150-F)
IP Rating	IP00
Component Type Motor Control and Drives	LV Soft Starter
Rated Current, Light Duty, 3 Wire	135 A, 3 wire
Rated Current, Normal (Medium) Duty, 3 Wire	135 A, 3 wire
Rated Current, Heavy Duty, 3 Wire	108 A, 3 wire
Rated Current, Severe Duty, 3 Wire	91 A, 3 wire
Medium Duty Approx. kW (400/415 V AC, 3 wire)	75
Inbuilt Motor Protection	Yes, advanced
Bypass Contacts	Yes, internal
Control Voltage	24 V AC/DC

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-