

Catalogue No: **1734-IE2C**

POINT I/O 2AI CURRENT MODULE

Automation Systems > Distributed I/O and Signal Converters > Fieldbus I/O Systems > Allen-Bradley Point I/O™ > POINT I/O™ Modules > POINT I/O™ Analogue I/O Modules



Point I/O 2 Channel Analog Current Input Module, 24 V DC



- Up to 8 single-ended inputs or outputs per module
- Thermocouple and RTD modules available
- Individually configurable channels
- On-board scaling
- Selectable input filters
- Over-range and under-range detection

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	Point I/O (Bul. 1734)
Component Type Fieldbus I/O	I/O - Analogue Input Module
Number of Analogue Inputs	2 qty
Analogue Input Type(s)	Current: Single-Ended
Analogue Input Range(s)	0 ... 20mA 4 ... 20mA
Analogue Resolution, Input	16 bit (signed)
Power Supply	24V DC
Operating Temperature, Max	55 °C max
Operating Temperature, Min	-20 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-