



Point I/O 4 Channel Source Output Module, 24 V DC

- Input, output, and relay output modules
- Wide variety of voltages
- Point-level output fault states for short-circuit and wire-off diagnostics
- Field-side diagnostics on select modules
- Choice of direct-connect or rack-optimised communications
- POINT Guard I/O™ modules for safety applications
- Configurable modules - each point can be configured as a DC input or output
- DeviceLogix™ technology available

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|---------------------------------------|----------------------------|
| Product Series | Point I/O (Bul. 1734) |
| Component Type Fieldbus I/O | Digital Output Module |
| Number of Digital Outputs | 4 qty |
| Digital Output Type | 24V DC Sourcing (NPN) type |
| Digital Output Range | 10 ... 28.8V DC |
| Rated Current per Digital Output, Max | 1 A max, per DO |
| Rated Current per Module, Max | 3 A max, per module |
| Power Supply | 24V DC |
| Operating Temperature, Max | 55 °C max |
| Operating Temperature, Min | -20 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -40 °C min |
| Relative Humidity, Max | 95 %RH |
| Humidity Type | Non-condensing |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |