

Catalogue No: 1734-OW4

POINT I/O 4DO RELAY MODULE

Automation Systems > Distributed I/O and Signal Converters > Fieldbus I/O Systems > Allen-Bradley Point I/O™ > POINT I/O™ Modules > POINT I/O™ Digital I/O Modules



Representative Photo Only
(actual product may vary based on configuration selections)

Point I/O Coil NO DPST 4 Relay Module, 24 V DC

- Input, output, and relay output modules
- Wide variety of voltages
- Point-level output fault states for short-circuit and wire-off diagnostics
- Field-side diagnostics on select modules
- Choice of direct-connect or rack-optimised communications
- POINT Guard I/O™ modules for safety applications
- Configurable modules - each point can be configured as a DC input or output
- DeviceLogix™ technology available

SPECIFICATIONS

Product Series	Point I/O (Bul. 1734)
Component Type Fieldbus I/O	Digital Output Module
Number of Digital Outputs	4 qty
Digital Output Type	NO Relay type
Digital Output Range	5 ... 240V DC
Rated Current per Digital Output, Max	2 A max, per DO
Rated Current per Module, Max	8 A max, per module
Power Supply	24V DC
Operating Temperature, Max	55 °C max
Operating Temperature, Min	-20 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-