

Catalogue No: 1756-OA16

CONTROLLOGIX 16DO 74-265V AC MODULE

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® I/O Modules > ControlLogix® Digital I/O Modules



74-265 V AC Output 16 Pts (20 Pin)



- Variety of voltages
- 8 to 32 points per module
- Isolated and nonisolated module types
- Point-level output fault states
- Direct-connect or rack-optimized communication
- Field-side diagnostics on select modules

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	ControlLogix (Bul. 1756 / 1757)
Component Type PLC & I/O	Digital Output Module
Number of Digital Outputs	16 qty
Digital Output Type	120 / 240V AC type
Digital Output Range	74 ... 265V AC
Rated Current per Digital Output, Max	0.5 A max, per DO
Rated Current per Module, Max	4 A max, per module
Module Specific Functions	ControlLogix 120/240V AC output module, 16 mechanically fused/group (8 points/group)
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Vibration Acceleration (Max.)	2 m/s ²
Vibration Frequency, Operational (Max.)	500 Hz
Standards Compliance	IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-27 IEC 60068-2-30 IEC 60068-2-6 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-4-4 IEC 61000-4-5 IEC 61000-4-6 IEC 61000-6-4 IEEE C37.90.1

Catalogue No: **1756-OA16**
CONTROLLOGIX 16DO 74-265V AC MODULE

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® I/O Modules > ControlLogix® Digital I/O Modules



Certifications

CE
CSA
C-Tick
KC (KCC)
UL
FM

REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -