



Representative Photo Only  
(actual product may vary based on configuration selections)

**ControlLogix Power Supply 19-32V DC (10 Amp @ 5V)**

- All regulated voltages necessary for any ControlLogix® module to operate in the chassis
- Limited hold-up time for fluctuations in incoming line power
- Enables orderly system shutdown by signaling modules in the chassis of imminent voltage failure
- conformal coated options are available - contact NHP for further information

**SPECIFICATIONS**

|   |  |
|---|--|
| Product Series                          | ControlLogix (Bul. 1756 / 1757)  |
| Component Type PLC & I/O                | Power Supply   |
| Operating Temperature, Max              | 60 °C max  |
| Operating Temperature, Min              | 0 °C min   |
| Storage Temperature, Max                | 85 °C max  |
| Storage Temperature, Min                | -40 °C min   |
| Relative Humidity, Max                  | 95 %RH   |
| Vibration Acceleration (Max.)           | 2 m/s <sup>2</sup>   |
| Vibration Frequency, Operational (Max.) | 500 Hz   |
| Standards Compliance                    | IEC 60068-2-1<br>IEC 60068-2-14<br>IEC 60068-2-2<br>IEC 60068-2-27<br>IEC 60068-2-30<br>IEC 60068-2-6<br>IEC 61000-4-2<br>IEC 61000-4-29<br>IEC 61000-4-3<br>IEC 61000-4-4<br>IEC 61000-4-5<br>IEC 61000-4-6 |
| Certifications                          | ATEX<br>CE<br>CSA<br>C-Tick<br>FM<br>KC (KCC)<br>C-UL-US   |

Catalogue No: **1756-PB72**

**CONTROLLOGIX 19-32V DC 10A POWER SUPPLY**

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® Power Supplies



**REFERENCES**

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -