



ControlLogix Power Supply Redundant Chassis Adapter Module



- All regulated voltages necessary for any ControlLogix® module to operate in the chassis
- Limited hold-up time for fluctuations in incoming line power
- Enables orderly system shutdown by signaling modules in the chassis of imminent voltage failure
- conformal coated options are available - contact NHP for further information

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|---|--|
| Product Series | ControlLogix (Bul. 1756 / 1757) |
| Component Type PLC & I/O | Power Supply |
| Operating Temperature, Max | 60 °C max |
| Operating Temperature, Min | 0 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -40 °C min |
| Relative Humidity, Max | 95 %RH |
| Vibration Acceleration (Max.) | 2 m/s ² |
| Vibration Frequency, Operational (Max.) | 500 Hz |
| Standards Compliance | IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-27 IEC 60068-2-30 IEC 60068-2-6 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-6-4 |
| Certifications | ATEX CE CSA FM KC (KCC) RCM C-UL-US |

Catalogue No: **1756-PSCA2**

CONTROLLOGIX REDUNDANT POWER SUPPLY CHASSIS ADAPTER MODULE

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® Power Supplies



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -