

Catalogue No: **1769-IF16C**
COMPACTLOGIX 16AI CURRENT MODULE

Automation Systems > Modular Programmable Controllers > Compact PLC Systems > Allen-Bradley Bulletin 1769 CompactLogix™ > CompactLogix™ I/O Modules > CompactLogix™ Analogue I/O Modules



Representative Photo Only
(actual product may vary based on configuration selections)

CompactLogix 16 Channel Analog Current Input Module

- Current, voltage, thermocouple and RTD modules available
- Over-range and under-range detection
- Selectable response to a input sensor fault
- Optional ability to direct output device operation during an abnormal condition
- Individually configurable channels

SPECIFICATIONS	
Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Analogue Input Module
Number of Analogue Inputs	16 qty
Analogue Input Type(s)	Current: Single-Ended
Analogue Input Range(s)	0 ... 20mA 0 ... 21mA
Analogue Resolution, Input	16 bit (signed)
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
	Non-condensing

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-