



Representative Photo Only
(actual product may vary based on configuration selections)

CompactLogix 4 Channel Analog Current/Voltage Input Module

- Current, voltage, thermocouple and RTD modules available
- Over-range and under-range detection
- Selectable response to a input sensor fault
- Optional ability to direct output device operation during an abnormal condition
- Individually configurable channels

SPECIFICATIONS

| | |
|----------------------------|--|
| Product Series | CompactLogix (Bul. 1768 / 1769) |
| Component Type PLC & I/O | Analogue Input Module |
| Number of Analogue Inputs | 4 qty |
| Analogue Input Type(s) | Current / Voltage: Single-Ended / Differential |
| Analogue Input Range(s) | 0 ... 20mA 4 ... 20mA -10 ... 10V DC 0 ... 10V DC 0 ... 5V DC 1 ... 5V DC |
| Analogue Resolution, Input | 15 bit (signed) |
| Operating Temperature, Max | 60 °C max |
| Operating Temperature, Min | 0 °C min |
| Storage Temperature, Max | 85 °C max |
| Storage Temperature, Min | -40 °C min |
| Relative Humidity, Max | 95 %RH |
| Humidity Type | Non-condensing |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |