



Representative Photo Only  
(actual product may vary based on configuration selections)

**COMPACTLOGIX 4AI/2AO CURRENT/VOLTAGE MODULE**

- Current, voltage, thermocouple and RTD modules available
- Over-range and under-range detection
- Selectable response to a input sensor fault
- Optional ability to direct output device operation during an abnormal condition
- Individually configurable channels

**SPECIFICATIONS**

Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Analogue In/Out Module
Number of Analogue Inputs	4 qty
Analogue Input Type(s)	Current / Voltage: Single-Ended / Differential
Analogue Input Range(s)	0 ... 20mA 0 ... 10V DC
Analogue Resolution, Input	9 bit (signed)
Number of Analogue Outputs	2 qty
Analogue Output Type(s)	Current / Voltage: Single-Ended
Analogue Output Range(s)	0 ... 20mA 0 ... 10V DC
Analogue Resolution, Output	9 bit (signed)
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

# Catalogue No: **1769-IF4XOF2**

## COMPACTLOGIX 4AI/2AO CURRENT/VOLTAGE MODULE

Automation Systems > Modular Programmable Controllers > Compact PLC Systems > Allen-Bradley Bulletin 1769 CompactLogix™ > CompactLogix™ I/O Modules > CompactLogix™ Analogue I/O Modules



### REFERENCES

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue & Product Selection: -