

Catalogue No: **1769-IQ32**
COMPACTLOGIX 32DI 10-30V DC MODULE

Automation Systems > Modular Programmable Controllers > Compact PLC Systems > Allen-Bradley Bulletin 1769
CompactLogix™ > CompactLogix™ I/O Modules > CompactLogix™ Digital I/O Modules



Representative Photo Only
(actual product may vary based on configuration selections)

CompactLogix 32 Point 24V DC Input Module

- AC and DC modules available
- I/O density from 8 to 32 points per module
- Solid state and relay contact output modules available
- High speed input modules
- Input filtering is standard
- Optical isolation available

SPECIFICATIONS	
Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Digital Input Module
Number of Digital Inputs	32 qty
Digital Input Type	24V DC Sinking/Sourcing type
Type, Digital Input	24V DC Snk/Src type
Digital Input Range	10 ... 26.4V DC
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-