



Representative Photo Only
(actual product may vary based on configuration selections)

CompactLogix 6 Channel Thermocouple/Mv Input Module

- Current, voltage, thermocouple and RTD modules available
- Over-range and under-range detection
- Selectable response to a input sensor fault
- Optional ability to direct output device operation during an abnormal condition
- Individually configurable channels

SPECIFICATIONS

Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Analogue Input Module
Number of Analogue Inputs	6 qty
Analogue Input Type(s)	Thermocouple / mV
Analogue Input Range(s)	-50 ... 50mV DC -100 ... 100mV DC Type B Type C Type E Type J Type K Type N Type R Type S Type T
Analogue Resolution, Input	Configuration Dependent
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

Catalogue No: **1769-IT6**

COMPACTLOGIX 6AI THERMOCOUPLE/MV MODULE

Automation Systems > Modular Programmable Controllers > Compact PLC Systems > Allen-Bradley Bulletin 1769 CompactLogix™ > CompactLogix™ I/O Modules > CompactLogix™ Analogue I/O Modules



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -