



Representative Photo Only
(actual product may vary based on configuration selections)

CompactLogix 2 Channel Analog Current/Voltage Output Module

- Current, voltage, thermocouple and RTD modules available
- Over-range and under-range detection
- Selectable response to a input sensor fault
- Optional ability to direct output device operation during an abnormal condition
- Individually configurable channels

SPECIFICATIONS

Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Analogue Output Module
Number of Analogue Outputs	2 qty
Analogue Output Type(s)	Current / Voltage: Single-Ended
Analogue Output Range(s)	-10 ... 10V DC 0 ... 10V DC 0 ... 5V DC 1 ... 5V DC 0 ... 20mA 4 ... 20mA
Analogue Resolution, Output	14 bit (signed)
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-