



Representative Photo Only
(actual product may vary based on configuration selections)

PowerFlex 4 AC Drive, 240V AC, 1PH Input, 4.5 Amps, 0.75 kW, 1 HP, Frame Size A, IP20 (Open), LED Display, Fixed Digital Keypad, With Internal CE Compliant Filter, RS485

- Easy to start up and use - includes an integral keypad with a quick-start set of parameters making startup fast and easy. The keypad control keys and local potentiometer are active out of the box, further simplifying startup.
- Easy to program - the 12 most common parameters are grouped together to simplify programming. It is also compatible with Connected Components Workbench™ software for programming and monitoring of the drive.
- Easy to install - features compact packaging that can either DIN rail or panel mounted.
- Space saving - allows for Zero-Stacking™, enabling multiple drives to be mounted side-by-side saving valuable panel space
- Simple networking - includes integral RS-485 communications, providing a very cost effective solution for simple multi-drop network solutions.

SPECIFICATIONS	
Shock Acceleration (Max.)	15 g
Shock Duration (Max.)	11 ms
Vibration Acceleration (Max.)	1 m/s²
Vibration Frequency, Operational (Max.)	2000 Hz

REFERENCES	
IECEEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-