

Catalogue No: **440G-L07264**

ATLAS 5 2NC-SFTY 1NO-AUX 2NO/1NC-SOLENOID 24V AC/DC

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley Mechanical Interlocks > Guard-Locking Interlock Switches > Atlas 5



Representative Photo Only
(actual product may vary based on configuration selections)

Guard Locking Switch - Atlas 5 solenoid voltage: 24V AC/DC, 2N/C 1N/O, includes actuator

- Available in tongue-interlocking or solenoid-based guard interlocking types
- Heads are rotatable for optimum mounting flexibility
- Suitable for sliding, hinged or lift-off guards

SPECIFICATIONS

Safety Switch Type	Guard Locking Switch type
Interlock Type	Tongue-Operated type
Number of Safety Contacts	2 qty safety
Output Configuration, Safety	2 NC
Number of Aux Contacts	1
Output Configuration, Auxiliary	1 NO
Solenoid Voltage, AC/DC, Nom	24 V AC/DC
Holding Force, Max	5000 N
Conduit Entry	M20 entry
Actuator Included	Yes Y / N
Actuator Type	Standard (fixed) tongue
Includes actuator guide	No Y / N
Un, Nominal Operational Voltage, AC	24 V AC
Un, Nominal Operational Voltage, DC	24 V DC
Material, Body / Housing	Alloy, Die-Cast material
Ex Rated	No
Operating Temperature, Max	60 °C max
Operating Temperature, Min	-10 °C min
Storage Temperature, Max	60 °C max
Storage Temperature, Min	-10 °C min
IP Rating	IP65
Standards Compliance	EN 60947-5-1 IEC 60947-5-1 IEC/EN 60204-1 Stop Category 0 IEC/EN 60204-1 Stop Category 1 IEC/EN 60204-1 Stop Category 2 AS/NZS 4024 Category 1 EN 954 / ISO 13849:1999 Category 1

Catalogue No: **440G-L07264**

ATLAS 5 2NC-SFTY 1NO-AUX 2NO/1NC-SOLENOID 24V AC/DC

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley Mechanical Interlocks > Guard-Locking Interlock Switches > Atlas 5



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -