

Catalogue No: **440G-S36005**

SPARTAN SWITCH PWR RLS 2NC 1NO 230V AC/DC

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley Mechanical Interlocks > Guard-Locking Interlock Switches > Spartan



Guard Locking Switch - 440G-MT: Solenoid Voltage: 230V AC/DC, Contacts(Safety and Aux): 2 Normally Closed, 1 Normally Open, Actuator: Standard, Conduit Entry: M20 Conduit



Representative Photo Only
(actual product may vary based on configuration selections)

- Available in tongue-interlocking or solenoid-based guard interlocking types
- Heads are rotatable for optimum mounting flexibility
- Suitable for sliding, hinged or lift-off guards

SPECIFICATIONS

Safety Switch Type	Guard Locking Switch type
Number of Safety Contacts	2 qty safety
Solenoid Voltage, AC/DC, Nom	230 V AC/DC
Holding Force, Max	1200 N
Conduit Entry	1 x M20 entry
Actuator Included	Yes Y / N
Actuator Type	Standard (fixed) tongue
Includes actuator guide	No Y / N
Material, Body / Housing	Alloy, Die-Cast material
Ex Rated	No
IP Rating	IP67

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-