
Catalogue No: **700-HK32A24-4**

MINIATURE INDUSTRIAL RELAY 8A 2CO 24VAC COIL W/LED

Timers and Control Relays > General Purpose Relays > Electromechanical Relays > Allen-Bradley Electromechanical Relays > 700-HK Miniature Relays > 7





SPECIFICATIONS

Slim Line Relay, 8 A Contact, DPDT, 24 V AC, Pilot Light

- Tested to a range of international standards to ensure compliance and reliability in application
- Wide range of relays that provides reliable design, quick replacements and panel space-saving solutions
- Various types of relays in the range which cover application requirements from PLC switching to high current loads

Product Series Bul. 700-HK Component Type Timers and Control relays Relay **Contact Configuration** 2 CO In. Rated Current 8 A Contact Breaking Capacity, DC1, 30V 12 A le, Rated Operational Current, AC-1, 250V 8 A@250V Rated Load, AC-1 2000 VA le, Rated Operational Current, AC-15, 230V 1.52 A@230V Rated Load, AC-15 350 VA Coil Type AC Additional Features Pilot Light Coil Voltage, AC, Nom 24 V AC Coil Voltage, AC, Min 19.2 V AC Coil Voltage, AC, Max 26.4 V AC Material, Contacts Silver Nickel (AgNi) material Mechanical Service Life 10000000 cycles Electrical Service Life at Un, In 30000 cycles IP Rating IP20 **Total Making Time** 15 ms **Total Breaking Time** 5 ms Insulation Voltage, between Coil & Contacts 250 V Dielectric Strength, between open Contacts 2000 V AC Mounting Plug-in -40 °C min Operating Temperature, Min 70 °C max Operating Temperature, Max -40 °C min Storage Temperature, Min



Storage Temperature, Max

Height

85 °C max 30.1 mm

Catalogue No: **700-HK32A24-4**

MINIATURE INDUSTRIAL RELAY 8A 2CO 24VAC COIL W/LED





Width	29 mm
Depth	12.4 mm
Shock Acceleration (Max.)	50 g
Vibration Acceleration (Max.)	5 m/s²
Vibration Displacement (Peak to Peak Max	x.) 0.76 mm
Vibration Frequency, Operational (Max.)	2000 Hz
Standards Compliance	EN 61810-1 CSA C22.2 No. 14 UL 508
Certifications	CSA C-UL-US Functional Safety Listed
REFERENCES	
IECEx Certificate -	
Supplier Declaration of Conformity:	
Installation Guide: -	
User Manual: -	
Manufacturer Datasheet: -	
Manufacturer Catalogue - & Product Selection:	

