

# Catalogue No: **889D-F4ACDM-10**

## CABLE PVC YELLOW 4PIN 22AWG DC-MICRO-M DC-MICRO-F 10M

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Pre-Wired Cables and Connection Systems > Allen-Bradley Connection systems > DC Micro, 4-Pin > Patchcords



Patchcord: DC Micro (M12), Female, Straight, 4-Pin, PVC Cable, Yellow, Unshielded, 22 AWG, IEC Color Coded, DC Mic, Male, Straight, 10 m (32.8 ft.)



Representative Photo Only  
(actual product may vary based on configuration selections)

### SPECIFICATIONS

Product Series	889 Cordsets and Patchcords
Component Type Termination Wiring	Patchcord (Connector at Each End)
Connector A	M12 x 1, DC Micro, 4-pin
Orientation, Connector A	Straight Through ConnectorA
Gender, Connector A	Female ConnectorA
Connector B	M12 x 1, DC Micro, 4-pin
Orientation, Connector B	Straight Through ConnectorB
Gender, Connector B	Male ConnectorB
In, Rated Current	4 A
Ue, Rated Operational Voltage, AC, max	250 V AC
Material, Contacts	Gold-Plated Brass material
Bend Radius	50 mm
Material, Coupling Nut	Epoxy-Coated Zinc
Material, cable jacket	PVC material
Colour, Cable Jacket	Yellow colour
Diameter, Cable Jacket	5 mm
Number of Conductors	4 qty
Wire / Conductor Size	22 AWG ( 0.326 mm <sup>2</sup> )
Length, Cable	10 m
IP Rating	IP69K
Operating Temperature, Min	-20 °C min
Operating Temperature, Max	105 °C max

# Catalogue No: **889D-F4ACDM-10**

## CABLE PVC YELLOW 4PIN 22AWG DC-MICRO-M DC-MICRO-F 10M

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Pre-Wired Cables and Connection Systems > Allen-Bradley Connection systems > DC Micro, 4-Pin > Patchcords



### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -